PORTABLE EV CHARGER

MODEL 7KW

Single Phase Type 2 Adjustable from 6A to 32A

Technical specifications.

- RCM Certification
- 6-32A Adjustable Current
- Relay Welding Inspection
- Internal Temperature Detection and Protection
- Scheduled and Delayed Charging
- Easy Installation and Maintenance
- Type A+DC6mA
- IP66
- 7 Metre Cable
- LCD + LED Indicator
- Touch Button
- Single-Phase Mode 2

Model	
Part Number	7KWPLEDT
AC Power (Adjustable)	7.4kW 6A / 10A / 13A / 16A / 20A / 24A /32A
Supply	230V+ / -10% 50Hz+ / 2%
Settings Available	Current selection, scheduled charging
Operating Temperature	-25° to +50°C
Storage (Dry Conditions)	-40° to 80°C
Humidity	<93>RH+ / -3%RH
Protection	Over current, Over / Under voltage Over temperature: >70°C the charger reduces output to 6A. >75° the charger shuts down
Sinusoidal Wave Form Distortion	<5%
Thermal Monitoring	i) Input plug temperature ii) Relay & internal temperature
Relay Welding	Alarm and shutdown protection
Humidity	5%-90% RH non condensing
LED	3 colour LED for power, charging and fault
Dimensions	246 x 81 x 50mm
Applicable Safety Standards	IEC62196-2 / IEC62752